

bizhub 550i

Black & White A3 multifunctional









CUSTOMER BENEFITS



Security

Secure network integration, data encryption, hard drive overwrite and advanced user authentication



Productivity

Reliability, high-speed scanning and printing, combined with powerful finishing functions



Sustainability

Numerous eco features reduce energy consumption and costs



Intuitive operability Operate the bizhub like a

smartphone or tablet with fully customized user interface



Application ecosystem Enhanced efficiency thanks

to Konica Minolta's extensive applications portfolio



Services

Efficient printer fleet management, including automatic consumables delivery, pro-active maintenance and remote setup

OPTIONS



PDF enhancements

OCR text recognition

Barcode fonts LK-106

Unicode fonts


OCR A and B fonts

Document converter pack

ThinPrint® client

Antivirus LK-116 FOIP IP Fax (T.38)





ID card reader Mount kit MK-735

3 OTHERS

Working table

10-Key pad Security kit

Replacement SSD

Keyboard holder KH-102

MEDIA INPUT

1x Universal tray PC-116 2x Universal tray

Large capacity tray PC-417

Large capacity tray Large capacity tray LU-207

Banner tray

5 MEDIA OUTPUT

Output tray OT-513

Attachment kit MK-607

Staple finisher FS-539

ınch kit for FS-539/SD

Staple finisher FS-540

Punch kit for FS-540/SD PK-526

OR)

Post inserter for FS-540/SD PI-507 Job separator for FS-540/SD OR

Z-fold unit for FS-540/SD

LEGEND

Option

respective option

Mandatory option

This option can only be installed with the above it

FINISHING FUNCTIONALITIES































stapling

stapling

punching

punching

Duplex

Combined mixplex/ mixmedia

Half-fold

insertion

Tri-fold

Booklet

Offset sorting

printing

Stapling

DESCRIPTION

| ENHANCED FEATURES | |
|----------------------------------|-----------------------------------------------------------|
| LK-102v3 PDF enhancements | PDF/A(1b), PDF encryption, digital signature |
| LK-105v4 OCR text recognition | Searchable PDF and PPTX |
| LK-106 Barcode fonts | Supports native barcode printing |
| LK-107 Unicode fonts | Supports native Unicode printing |
| LK-108 OCR A and B fonts | Supports native OCR A and B font printing |
| LK-110v2 Document converter pack | Generates various file formats incl. DOCX, XLSX and PDF/A |
| LK-111 ThinPrint® client | Print data compression for reduced network impact |
| LK-116 Antivirus | Bitdefender® antivirus provides real time scanning of all |
| | incoming and outgoing data |
| LK-117 FOIP activation | Fax over IP networks (T.38), requires fax kit |
| | |
| CONNECTIVITY | |
| FK-514 Fax board | Super G3 fax, digital fax functionality |
| UK-221 Wireless LAN | Wireless LAN and wireless LAN Access Point Mode |
| EK-608 USB I/F kit | USB keyboard connection |
| EK-609 USB I/F kit | USB keyboard connection; Bluetooth |
| AU-102 Biometric authentication | Finger vein scanner |
| ID card reader | Various ID card technologies |
| MK-735 Mount kit | Installation kit for ID card reader |
| | |
| OTHERS | |
| WT-506 Working table | Authentication device placement |
| KP-102 10-Key pad | For use instead of touchscreen |
| SC-509 Security kit | Copy guard function |
| EM-908 Replacement SSD | 1 TB SSD to increase storage space |
| | |

To place USB keyboard

Auto detects paper weight and type

500 sheets, 5.5" x 8.5" – 11" x 17" / 52–256 g/m 2

| PC-216 2x Universal tray | 2x 500 sheets, 5.5" x 8.5" - 11" x 17" / 52-256 g/m ² |
|------------------------------------|---------------------------------------------------------------------------|
| PC-416 Large capacity tray | 2,500 sheets, 8.5" x 11" / 52–256 g/m ² |
| PC-417 Large capacity tray | 1,500 + 1,000 sheets, 5.5" x 8.5" or 8.5" x 11" / 52–256 g/m ² |
| LU-302 Large capacity tray | 3,000 sheets, 8.5" x 11" / 52–256 g/m ² |
| LU-207 Large capacity tray | 2,500 sheets, 8.5" x 11" – 12" x 18" / 52–256 g/m ² |
| MK-730 Banner tray | Multipage banner feeding |
| MEDIA OUTPUT | |
| OT-513 Output tray | Output tray used instead of finisher |
| JS-508 Job separator | Separation of fax output; etc. |
| FS-533 Inner finisher | 50-sheet stapling, 500 sheets max. output |
| MK-607 Attachment kit | For FS-533 installation |
| PK-519 Punch kit for FS-533 | 2/3-hole punching, auto switching |
| FS-539 Staple finisher | 50-sheet stapling; 3,200 sheets max. output |
| FS-539SD Booklet finisher | 50-sheet stapling; 20 sheets booklet finisher; |
| | 2,200 sheets max. output |
| PK-524 Punch kit for FS-539/SD | 2/3-hole punching; auto switching |
| FS-540 Staple finisher | 100 sheets stapling; 3,200 sheets max. output |
| FS-540SD Booklet finisher | 100 sheets stapling; 20 sheets booklet finisher; |
| | 2,700 sheets max. output |
| PK-526 Punch kit for FS-540/SD | 2/3-hole punching; auto switching |
| RU-513 Relay unit | For FS-539/SD or FS-540/SD installation |
| JS-602 Job separator for FS-540/SD | Separation of fax output; etc. |
| PI-507 Post inserter for FS-540/SD | Cover insertion; post finishing |
| ZU-609 Z-fold unit for FS-540/SD | Z-fold for 11" x 17" prints |

TECHNICAL SPECIFICATIONS

KH-102 Keyboard holder

PC-116 1x Universal tray

IM-102 Intelligent media sensor

MEDIA INPUT

SYSTEM SPECIFICATIONS System speed 8.5" x11" Up to 55 ppm System speed 11" x 17" Up to 27 ppm Autoduplex speed 8.5" x 11" Up to 55 ppm 1st page out time 8.5" x 11" 3.3 sec. Warm-up time Approx. 14 sec.1 Imaging technology Toner technology Simitri® HD polymerized toner Panel size/resolution 10.1" / 1024 x 600 8,192 MB (standard/max) System memory System hard drive 256 GB SSD (standard) / 1 TB SSD (optional) 10/100/1,000-Base-T Ethernet; Interface USB 2.0; Wi-Fi 802.11 b/g/n/ac (optional) Network protocols TCP/IP (IPv4/IPv6); SMB; LPD; IPP; SNMP; HTTP(S) Automatic document feeder Up to 300 originals / 5.5" x 8.5" – 11" x 17" / 35-210 g/m² / Dual scan ADF ADF double feed detection Standard Printable paper size 3.5" x 5.5" – 12" x 18" / customized paper sizes / banner paper max. 47.2" x 11.7" 52-300 g/m² Printable paper weight Paper input capacity 1,150 sheets / 6,650 sheets (standard/max) Paper tray input (standard) $1 \times 500 / 3.5$ " x 5.8" – 11" x 17" / custom sizes / 52-256 g/m² 1 x 500 / 5.5" x 8.5" - 12" x 18" / custom sizes / 52-256 g/m² 1 x 500 / 5.5" x 8.5" – 11" x 17" / 52–256 g/m² Paper tray input (optional) $2 \times 500 / 5.5$ " x 8.5" – 11" x 17"/ 52– $256 \, g/m^2$ $1\,x\,2,500\,/\,8.5"\,x\,11"\,/52-256\,g/m^2$

52-256 g/m²

1 x 1,500 + 1 x 1,000 sheets / 5.5" x 8.5" or 8.5" x 11" /

| 3131LW 3F LCII ICATIONS | |
|--------------------------------|----------------------------------------------------------------------------|
| Large capacity tray (optional) | 1 x 3,000 / 8.5" x 11" / 52-256 g/m ² |
| | 1 x 2,500/8.5" x 11" – 12" x 18" / custom sizes / |
| | 52-256 g/m ² |
| Manual bypass | 150 sheets / 3.5" x 5.5" – 12" x 18" / custom sizes / |
| | banner / 60–300 g/m² |
| Finishing modes (optional) | Offset; Group; Sort; Staple; Staple (offline); Punch; Half-fold; |
| | Letter-fold; Booklet; Post insertion; Z-fold |
| Automatic duplexing | 4.1" x 5.5" – 12" x 18" / 52–256 g/m ² |
| Output capacity | Up to 250 sheets / up to 3,300 sheets (standard/max) |
| Stapling | Max. 100 sheets or 98 sheets + 2 cover sheets (up to 300 g/m^2) |
| Stapling output capacity | Max. 200 sets |
| Letter fold | Max. 3 sheets |
| Letter fold capacity | Max. 50 sets; unlimited (without tray) |
| Booklet | Max. 20 sheets or 19 sheets + 1 cover sheet (up to 300 g/m^2) |
| Booklet output capacity | Max. 35 booklets; unlimited (without tray) |
| Duty cycle (monthly) | Rec. 50,000 pages; Max. ² 200,000 pages |
| Toner lifetime | Black up to 24,000 pages |
| Imaging unit lifetime | Black up to 240,000/1,000,000 pages (drum/developer) |
| Power consumption | 220-240 V / 50/60 Hz; Less than 2.00 kW |
| System dimension (W x D x H) | 24.2" x 27.1" x 37.8" (without options) |
| System weight | Approx. 220 lb (without options) |
| | |

SYSTEM SPECIFICATIONS

PRINTER SPECIFICATIONS

| Print resolution | 1,800 (equivalent) x 600 dpi; 1200 x 1200 dpi |
|---------------------------|-------------------------------------------------------------|
| Page description language | PostScript 3 (CPSI 3016); PCL 6 (XL3.0); PCL 5c; XPS |
| Operating systems | Windows 7 (32/64); Windows 8.1 (32/64); Windows 10 (32/64); |
| | Windows Server 2008 (32/64); Windows Server 2008 R2; |
| | Windows Server 2012; Windows Server 2012 R2; |
| | Windows Server 2016; Windows Server 2019; |
| | Macintosh OS X 10.10 or later; Linux |
| Printer fonts | 80 PCL Latin; 137 PostScript 3 Emulation Latin |
| Mobile printing | Konica Minolta Print Service (Android); |
| | Konica Minolta Mobile Print (iOS/Android); |
| | AirPrint (iOS); Mopria (Android) |
| | optional: WiFi Direct |
| | |

SCANNER SPECIFICATIONS

| | · · · |
|-------------------|---------------------------------------------------------|
| Scan speed | Up to 140 ipm in simplex (mono) |
| | Up to 280 ipm in duplex (mono) |
| Scan resolution | Up to 600 x 600 dpi |
| Scan modes | Scan-to-eMail (Scan-to-Me); Scan-to-SMB (Scan-to-Home); |
| | Scan-to-FTP; Scan-to-Box; Scan-to-USB; Scan-to-WebDAV; |
| | Scan-to-DPWS; Scan-to-URL; TWAIN scan |
| File formats | JPEG; TIFF; PDF; Compact PDF; Encrypted PDF; XPS; PPTX |
| | optional: Searchable PDF; PDF/A 1a and 1b; |
| | Searchable DOCX/PPTX/XLSX |
| Scan destinations | 2,000 destinations + 100 groups; LDAP support |

COPIER SPECIFICATIONS

| Copy resolution | 600 x 600 dpi |
|-----------------|-------------------------------------|
| Gradation | 256 gradations |
| Multicopy | 1–9,999 |
| Original format | Max. 11" x 17" |
| Magnification | 25–400% in 0.1% steps; Auto-zooming |

FAX SPECIFCIATION

| Fax standard | Super G3 (optional) |
|------------------|------------------------------------|
| Fax transmission | Analog; i-Fax; Color i-Fax; IP-Fax |
| Fax resolution | Up to 600 x 600 dpi |
| Fax compression | MH; MR; MMR; JBIG |
| Fax modem | Up to 33.6 Kbps |
| Fax destinations | 2,000 single + 100 groups |























For complete information on Konica Minolta products and solutions, please visit: CountOnKonicaMinolta.com

USER BOX SPECIFICATIONS

| Storable documents | Up to 3,000 documents or 10,000 pages |
|----------------------|-------------------------------------------------------------------|
| Type of user boxes | Public; Personal (with password or authentication); |
| | Group (with authentication) |
| Type of system boxes | Secure print; Encrypted PDF print; Fax receipt; Fax polling |
| SYSTEM FEATURES | |
| Security | ISO 15408 HCD-PP Common Criteria (in evalutation); |
| | IP filtering and port blocking; SSL3 and TLS1.0/1.1/1.2 network |
| | communication; IPsec support; IEEE 802.1x support; |
| | User authentication; Authentication log; Secure print; Kerberos; |
| | Hard drive overwrite; Hard drive data encryption (AES 256); |
| | Confidential fax; Print user data encryption |
| | optional: Antivirus realtime scanning (Bitdefender®); |
| | Copy protection (Copy Guard, Password Copy) |
| Accounting | Up to 1,000 user accounts; Active Directory support (user name + |
| | password + e-mail + smb folder); User function access definition; |
| | Authentication by mobile device (Android) |
| | optional: Biometric authentication (finger vein scanner); |
| | ID card authentication (ID card reader); |
| | Authentication by mobile device (iOS) |
| Software | Net Care Device Manager; Data Administrator; Box Operator; |
| | Web Connection; Print Status Notifier; Driver Packaging Utility; |
| | Log Management Utility |
| | |

- All specifications refer to 8.5" x 11"-size paper of 80 g/m 2 quality.
- The support and availability of the listed specifications and functionalities varies depending on operating systems, applications and network protocols as well as network and system configurations.
- The stated life expectancy of each consumable is based on specific operating conditions such as page coverage for a $particular\ page\ size\ (5\%\ coverage\ of\ 8.5''\ x\ 11'').\ The\ actual\ life\ of\ each\ consumable\ will\ vary\ depending\ on\ use\ and$ $other \ printing \ variables \ including \ page \ coverage, \ page \ size, \ media \ type, \ continuous \ or \ intermittent \ printing, \ ambient$ temperature and humidity.
- Some of the product illustrations contain optional accessories.
- Specifications and accessories are based on the information available at the time of printing and are subject to change
- Konica Minolta does not warrant that any specifications mentioned will be error-free.
- All brand and product names may be registered trademarks or trademarks of their respective holders and are hereby acknowledged.



KONICA MINOLTA BUSINESS SOLUTIONS U.S.A., INC. 100 Williams Drive, Ramsey, New Jersey 07446

CountOnKonicaMinolta.com









¹ Warm-up time may vary depending on the operating environment and usage

² If the maximum volume is reached within a period of one year, then a maintenance cycle must be performed